

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An apparatus comprising a processor programmed to generate a user interface comprising the following elements:

a main folder configured to contain a plurality of elements;

at least a first sequential subfolder configured to contain a plurality of elements linked to the main folder, the first sequential subfolder being displayable in the form of a carousel having more elements than can be displayed at one time in a display region, wherein the carousel is displayable as a plurality of carousel elements that rotate around a carousel axis;

a fixed focus pointer configured to select one of the plurality of elements of the main folder in response to interaction of a user; and

at least one moveable focus pointer configured to scroll through the plurality of elements of the at least first sequential subfolder to select one of the plurality of elements in response to interaction of a user.

2. (Previously Presented) The apparatus of claim 1, wherein one element of the carousel is configured to create a buffer for elements that are not presented.

3. (Original) The apparatus of claim 2, wherein the element has a fixed position.

4. (Original) The apparatus of claim 3, wherein the buffer element is placed in the middle of a rear carousel segment.

5. (Original) The apparatus of claim 4, wherein the element is visible.

6. (Original) The apparatus of claim 4, wherein the element is not visible.

7. (Previously Presented) The apparatus of claim 2, wherein the element is configured to indicate the number of elements in the buffer.

8. (Original) The apparatus of claim 1, wherein a diameter of the carousel is adjustable.

9. (Previously Presented) The apparatus of claim 8, wherein the diameter of the carousel is adjustable as a function of the number of the plurality of elements of the first sequential subfolder.

10. (Previously Presented) The apparatus of claim 9, wherein the carousel is configured to be not fully presented on the display.

11. (Previously Presented) The apparatus of claim 10, wherein an uppermost portion of the carousel is configured to be not present on a display region.

12. (Currently Amended) The apparatus of claim 10, wherein a lowermost portion of the carousel is configured to be not present on a display region.

13. (Previously Presented) The apparatus of claim 10, wherein an uppermost portion and a lowermost portion of the carousel are configured to be not present on a display region.

14. (Previously Presented) The apparatus of claim 1, wherein information of content of elements is configured to be visible.

15. (Original) The apparatus of claim 1, wherein the elements in the carousel are selectable.

16. (Original) The apparatus of claim 1, wherein the plurality of elements of the main folder and the at least first subfolder comprise icons.

17. (Original) The apparatus of claim 1, wherein the plurality of elements of the main folder and the at least first subfolder comprise text.

18. (Original) The apparatus of claim 1, wherein the main folder and at least first sequential subfolder are scrollable.

19. (Cancelled).

20. (Currently Amended) A method comprising:

generating a main folder of a user interface for display on a display device, wherein the main folder is configured to contain a plurality of elements;

generating at least a first sequential subfolder configured to contain a plurality of elements linked to the main folder, the first sequential subfolder being displayable in the form of a carousel having more elements than can be displayed at one time in a display region, wherein the carousel is displayable as a plurality of carousel elements that rotate around a carousel axis;

generating a fixed focus pointer configured to select one of the plurality of elements of the main folder in response to interaction of a user; and

generating at least one moveable focus pointer configured to scroll through the plurality of elements of the at least first sequential subfolder to select one of the plurality of elements in response to interaction of a user.

21. (Cancelled).

22. (New) The method of claim 20, wherein one element of the carousel is configured to create a buffer for elements that are not presented.

23. (New) The method of claim 22, wherein the element has a fixed position.

24. (New) The method of claim 23, wherein the buffer element is placed in the middle of a rear carousel segment.

25. (New) The method of claim 24, wherein the element is visible.

26. (New) The method of claim 24, wherein the element is not visible.

27. (New) The method of claim 22, wherein the element is configured to indicate the number of elements in the buffer.

28. (New) The method of claim 20, wherein a diameter of the carousel is adjustable.

29. (New) The method of claim 28, wherein the diameter of the carousel is adjustable as a function of the number of the plurality of elements of the first sequential subfolder.

30. (New) The method of claim 29, wherein the carousel is configured to be not fully presented on the display.

31. (New) The method of claim 30, wherein an uppermost portion of the carousel is configured to be not present on a display region.

32. (New) The method of claim 30, wherein a lowermost portion of the carousel is configured to be not present on a display region.

33. (New) The method of claim 30, wherein an uppermost portion and a lowermost portion of the carousel are configured to be not present on a display region.

34. (New) An apparatus comprising:

means for generating a main folder of a user interface for display on a display device, wherein the main folder is configured to contain a plurality of elements;

means for generating at least a first sequential subfolder configured to contain a plurality of elements linked to the main folder, the first sequential subfolder being displayable in the form of a carousel having more elements than can be displayed at one time in a display region, wherein the carousel is displayable as a plurality of carousel elements that rotate around a carousel axis;

means for generating a fixed focus pointer configured to select one of the plurality of elements of the main folder in response to interaction of a user; and

means for generating at least one moveable focus pointer configured to scroll through the plurality of elements of the at least first sequential subfolder to select one of the plurality of elements in response to interaction of a user.

35. (New) The apparatus of claim 34, wherein one element of the carousel is configured to create a buffer for elements that are not presented.

36. (New) The apparatus of claim 35, wherein the element is configured to indicate the number of elements in the buffer.

37. (New) The apparatus of claim 34, wherein a diameter of the carousel is adjustable.

38. (New) The apparatus of claim 37, wherein the diameter of the carousel is adjustable as a function of the number of the plurality of elements of the first sequential subfolder.